AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listing, of claims in the application:

Listing of Claims:

- 1. (Original) An apparatus for reproducing sound comprising: a body;
- a driver for reproducing a desired sound; and

an acoustic passageway having first and second passageway portions, the first passageway portion being defined by a portion of the body and the second passageway portion being defined by an exterior boundary.

- 2. (Original) An apparatus according to claim 1 wherein the first acoustic passageway portion comprises a horn located within the body of the apparatus.
- 3. (Original) An apparatus according to claim 1 wherein the body has exterior surfaces thereof and the boundary defining the second acoustic passageway portion comprises at least one of the exterior surfaces of the body or a boundary of the environment within which the apparatus is placed.
- 4. (Original) An apparatus according to claim 3 wherein the boundary of the environment is a wall, floor or ceiling.
- 5. (Original) An apparatus according to claim 1 wherein the body defines at least one handle for lifting or carrying the apparatus.

- 6. (Original) An apparatus according to claim 5 wherein the body is generally rectangular in shape and has a plurality of external surfaces and the handle has a first opening located on one side of the body and a second opening located on a second side of the body, the openings being connected to form a passage through the body of the apparatus.
- 7. (Original) An apparatus according to claim 6 wherein the first and second openings are located adjacent a corner of the body and form the corner of the body into a post to be grasped when lifting or carrying the apparatus.
- 8. (Original) An apparatus for reproducing sound comprising:
 a first speaker having a body defining a horn and a horn opening located in a corner thereof; and

a second speaker having a body defining a horn and a horn opening located in a corner thereof, the first and second speakers being positioned adjacent one another and having both horn openings generally adjacent one another to form a side-by-side array of speakers.

9. (Original) An apparatus according to claim 8 further comprising a second side-by-side array of speakers, the first and second arrays being positioned adjacent one another and having the horn openings located generally adjacent one another to form a four speaker array.

<u>10.</u> [[8.]] (Currently amended) A method for reproducing sound with a speaker, the method comprising:

providing a body having an acoustical passageway that defines a first portion of a horn; and

using boundaries external to the body to define a second portion of the horn to effectively increase the size of the horn.

11. [[9.]] (Currently amended) A method according to claim 10 [[8]] wherein the body has exterior surfaces thereof and the step of using boundaries external to the body comprises:

using at least one of the exterior surfaces of the body or a boundary of the environment within which the apparatus is placed to define the second portion of the horn.

- 12. [[10.]] (Currently amended) An method according to claim 10 [[8]] wherein using a boundary of the environment within which the apparatus is placed comprises using a wall, floor or ceiling to define at least a portion of the second portion of the horn.
- 13. [[11.]] (Currently amended) A kit for reproducing sound comprising: a body having a driver for reproducing a desired sound and an acoustic passageway having first and second passageway portions, the first passageway portion being defined by a portion of the body and the second passageway portion being defined by an exterior boundary; and

instructions for positioning the body in a manner that uses the exterior boundary to define the second passageway portion of the acoustic passageway.

- 14. (New) A apparatus for reproducing sound comprising:
 a body having a driver for reproducing sound, the body being generally rectangular in shape and having a plurality of external surfaces; and
- a handle having a first opening located on one side of the body and a second opening located on a second side of the body, the openings being connected to form a passage through the body of the apparatus.
- 15. (New) An apparatus according to claim 14 wherein the first and second openings are located adjacent a corner of the body and form the corner of the body into a post to be grasped when lifting or carrying the apparatus.